Magna-Patch

Quick-Set Patching Compound

A strong fast setting, concrete patching compound that dries in just 15-20 minutes.

- Permanent bond
- No shrinkage
- Fast setting
- Stronger than concrete
- Easy-to-use
- Many applications

Description

Areas of Application

- Government facilities
- Farms
- Food plants
- Public car parks
- Mechanics
- Golf courses
- Hospitals
- Roadway repair
- Industrial facilities
- Rental companies
- Roadway repair
- Shopping centres
- Warehouses

Directions
Apply MAGNA-PATCH at temperatures of 4°C - 32°C. The surface to be repaired or used for anchoring must be THOROUGHLY DRY. Do not dilute MAGNA-PATCH with water.

Coverage
5m² at 6mm thickness. If a small amount of MAGNA-PATCH is needed, mix 3 parts of Preactivated Granular with 1 part Hardener/Primer.

Technical Specifications	
Foot Traffic	15 – 20 minutes
Driveways	1-2 hours
Bridges	8 hours
Forklift Traffic Areas	24 Hours

Features and Benefits

Forms a permanent bond. It becomes part of the structure and doesn't shatter.

Sets faster than an epoxy. Its quick structural strength minimises downtime and traffic interruption.

Stronger than standard concrete with the same bulk density. It reaches standard concrete's strength in 1 day and will be up to twice as strong as some concretes within 28 to 30 days.

Easy to mix and apply and requires no special personnel or equipment.

Stronger than standard concrete with the same bulk density. It reaches standard concrete's strength in 1 day and will be up to twice as strong as some concretes within 28 to 30 days.

Excellent for repairing and rebuilding curbing, bridges, roadways, floors and other concrete surfaces, as well as for anchoring machinery and vibrating equipment.

WARNING: Consult the label for full instructions and precautions before using this product.

MANTEK®

CHEMSEARCH

Quality System
Quality
Endorsed
Company
AS/NZSISO 9001:2008
ISO 14000
QEC 11488