

De-moisturising and Anti-Corrosion Compound



Unique formula that penetrates, lubricates and seals out moisture.

- Quickly displaces moisture, oil, grease and surface grime
- Microscopic coating that shields against moisture and particulate contamination
- Protects electrical equipment against rust and corrosion

Description

Areas of Application

- Electrical
- Electronic equipment
- Motors
- Windings
- Ignition systems
- Multiple connectors
- Switch gears

Equipment Maintenance Directions

Apply one heavy coat of NC-123 Extra over all electrical equipment, internal and external areas including insulation, metal and painted surfaces.

Directions for Flood or Moisture-Damaged Equipment

1. Clean out debris and spray NC-123 Extra into windings, saturating all insulation and metal parts.
2. Continue spraying until the solution runs clear, indicating that all water has been removed.

Technical Specifications	
Flash Point	41.1°C
Spray Film Thickness	.00254 cm (similar to thin paint)
Resistant to	Water wash-out, salt action & spray

MEGA DISTRIBUTORS

PO Box 10185
North Shore Mail Centre
Auckland 0745
Phone: 09 473 6505
Fax: 09 473 6501
Email: sales@megadistributors.co.nz

www.megadistributors.co.nz

Features and Benefits

Eliminates moisture and corrosion build up. Inhibits moisture from entering into windings to maintain operating efficiency.

Can be applied to wet or dry surfaces of electrical equipment, internal and external areas including insulation, metals and painted surfaces. Evaporates with forced air.

Can be applied to all moving parts without drying and hardening. Cleans and lubricates equipment, even in use, to prevent squeaking.

Does not contain barium or chlorinated solvents and is safe for equipment and the environment.

WARNING: Consult the label for full instructions and precautions before using this product.

