

Dry Lubricant and Release Agent with Teflon™



Dries instantly to a noncorrosive, nonstaining, odourless and colourless thin film

- Eliminates sticking, squeaking and friction on most surfaces
- Provides a smooth, dry, friction-free surface
- Withstands extreme temperatures
- Contains no 1,1,1 - Trichloroethane

Description

Areas of Application

- Bushings
- Conveyors
- Platens
- Valves, latches, hinges
- Clamps
- Locks, latches, hinges
- Bearings
- Pulleys
- Woven belts

Directions

1. Allow TLR-44 Plus to air dry thoroughly.
2. Baking or heating is not necessary.

Precautions

1. Do not use in areas where it will contact aluminium paint or finely divided aluminium powder.
2. Do not use for torch tips.

Technical Specifications

Temperature Range	-40°C to 260°C
Melting Point	260°C
Penetration Point	Approximately 5 - 30 Seconds

Features and Benefits

Invisible lubricant and release agent that dries quickly to form a smooth, slick surface.

Effective in extreme temperature conditions ranging from -40°C to 260°C

Forms a protective barrier that repels water, oil, dirt and dust. TLR-44 Plus is also inert and will resist most acids and solvents.

TLR-44 Plus is highly versatile. It is safe to use on all metals plastics rubber, glass, paper and wood.

WARNING: Consult the label for full instructions and precautions before using this product.

MEGA DISTRIBUTORS

PO Box 10185
North Shore Mail Centre
Auckland 0745
Phone: 09 473 6505
Fax: 09 473 6501
Email: sales@megadistributors.co.nz

www.megadistributors.co.nz

